




# Balfit<sup>®</sup> 23 Series - NPT Male Two Piece - Non Skive - Stems

## Balfit<sup>®</sup> NPT Male - 23.0400

carbon steel, NPT (dry-seal taper thread) male fitting for crimping on high pressure hydraulic hoses



According to **SAE J516 / SAE J514**

**Material:** Carbon Steel, Trivalent Zink Plated - Rohs Compliant

**Ferrules:** Balfit Ferrule Series - 20.100, 20.101, 20.107, 20.200, 20.201, 20.202, 20.301, 20.302, 20.305

**Hoses:** Balflex Balflex Forza Uno - SAE 100R1AT/DIN EN 853 2SN

Balflex Forza Due - SAE 100R2AT/DIN EN 853 2SN

Balflex Balpac Premium - SAE 100R16/ DIN EN 853 2SC. Balpac 3000 - SAE 100R17/ DIN EN 853 1SC

Balflex textile braid hydraulic hose - SAE 100R3, SAE 100R6, DIN EN 854 1TE / 2TE / 3TE

Balflex thermoplastic hydraulic hoses - SAE100R7, SAE100R8 / DIN EN 855

Balflex PTFE stainless braid - 100R14

Balflex 2-MAX JACK / 3 MAX JACK

Balflex Balmaster - SAE 100R12 / DIN EN 856 4SP - on 1 1/4", 1 1/2" & 2"

part number	hose dash	hose Ø	thread	thread dash	C Cut Off	Hex.
		inch				
23-0302-MP	- 3	3/16"	1/8" - 27	- 2	22	12
23-0304-MP	- 3	3/16"	1/4" - 18	- 4	28	17
23-0402-MP	- 4	1/4"	1/8" - 27	- 2	23	12
23-0404-MP	- 4	1/4"	1/4" - 18	- 4	28	17
23-0406-MP	- 4	1/4"	3/8" - 18	- 6	28	19
23-0504-MP	- 5	5/16"	1/4" - 18	- 4	28	17
23-0506-MP	- 5	5/16"	3/8" - 18	- 6	28	19
23-0508-MP	- 5	5/16"	1/2" - 14	- 8	34	22
23-0604-MP	- 6	3/8"	1/4" - 18	- 4	28	17
23-0606-MP	- 6	3/8"	3/8" - 18	- 6	30	19
23-0608-MP	- 6	3/8"	1/2" - 14	- 8	35	22
23-0806-MP	- 8	1/2"	3/8" - 18	- 6	31	19
23-0808-MP	- 8	1/2"	1/2" - 14	- 8	35	22
23-0812-MP	- 8	1/2"	3/4" - 14	- 12	38	27
23-1012-MP	- 10	5/8"	3/4" - 14	- 12	38	27
23-1212-MP	- 12	3/4"	3/4" - 14	- 12	39	27
23-1216-MP	- 12	3/4"	1" - 11.1/2	- 16	44	36
23-1616-MP	- 16	1"	1" - 11.1/2	- 16	45	36
23-1620-MP	- 16	1"	1.1/4" - 11.1/2	- 20	50	46
23-2020-MP	- 20	1.1/4"	1.1/4" - 11.1/2	- 20	49	46
23-2424-MP	- 24	1.1/2"	1.1/2" - 11.1/2	- 24	51	50
23-3232-MP	- 32	2"	2" - 11.1/2	- 32	55	65

also available:

### Balfit<sup>®</sup> Stainless Steel NPT Male

(add an 'S' at the end of the part number; ex: 23.0400.0808 S)

#### Construction characteristics and dimensions may be changed at anytime without prior notice

The data contained herein is for information purposes only and does not enlarge, amend or imply any warranty other than provided by the manufacturer with the product.

Any use of the product not in conformance with the manufacturer's instruction may be dangerous

Only items in this catalog are carried in stock. Some items are subject to minimum quantities or sold in multiples of standard quantities. Please refer to the price list or contact our commercial department. Prices subject to change without notice.