



Balflex® HYDRAULIC AND INDUSTRIAL HOSE FLAT GUARD – 11.103.

High Density Polyethylene Protection Spring Guard Black Colour



Raw Material :	high density polyethylene resistant to abrasion and UV rays
Color :	black
Temperature range :	- 20°C (- 4°F) + 95°C (- 203°F)
Application :	protection of external rubber layer of hydraulic and industrial hoses, against the early wearing due to abrasion

Part number	Range	
	mm	inch
SG-09-15	9-15	0.35 – 0.59
SG-14-20	14-20	0.55 – 0.79
SG-18-24	18-24	0.71 – 0.94
SG-22-30	22-30	0.87 – 1.18
SG-30-38	30-38	1.18 – 1.50
SG-36-45	36-45	1.42 – 1.77
SG-44-65	44-60	1.73 – 2.36
SG-58-70	58-70	2.28 – 2.76
SG-65-78	65-78	2.56 – 3.08
SG-80-98	80-98	3.15 – 3.86
SG-96-116	96-116	3.78 – 4.57

Balflex® HYDRAULIC AND INDUSTRIAL HOSE FLAT GUARD – 11.103.Y

High Density Polyethylene Protection Spring Guard Yellow colour



Raw Material :	high density polyethylene resistant to abrasion and UV rays
Color :	yellow
Temperature range :	- 20°C (- 4°F) + 95°C (- 203°F)
Application :	protection of external rubber layer of hydraulic and industrial hoses, against the early wearing due to abrasion

Part number	Range	
	mm	inch
SG-09-15Y	9-15	0.35 – 0.59
SG-14-20Y	14-20	0.55 – 0.79
SG-18-24Y	18-24	0.71 – 0.94
SG-22-30Y	22-30	0.87 – 1.18
SG-30-38Y	30-38	1.18 – 1.50
SG-36-45Y	36-45	1.42 – 1.77
SG-44-65Y	44-60	1.73 – 2.36
SG-58-70Y	58-70	2.28 – 2.76
SG-65-78Y	65-78	2.56 – 3.08
SG-80-98Y	80-98	3.15 – 3.86
SG-96-116Y	96-116	3.78 – 4.57