




Balfit[®] 24 Series - Code 61 - Straight Flange Two Piece - Skive - High Pressure Stems

Skive: 100R12, 4SH, 4SP

Balfit[®] Spiral Straight SAE 3000 PSI (code 61) Flange - 24.7013

solid-piece, carbon steel (code 61) flanged fitting for crimping on high pressure hydraulic hoses



According to **ISO 6162** and **ISO 12151-3** According to **SAE J516** and **SAE J518**

Material : carbon steel, zinc plated

Ferrules : Balfit[®] ferrules series 20.400 and 20.403

Hoses : Balflex[®] **Balmaster** hoses **SAE 100R9R / SAE 100R12 / DIN EN 856 4SP**

may be also used on Balflex[®] Powerspir DIN EN 856 4SH hoses with Balfit ferrules series 20.403

| part number | hose dash | hose Ø | Flange size | flange dash | D Ø Flange | C Cut Off |
|------------------|-----------|--------|-------------|-------------|---------------|--------------|
| | | inch | inch | | mm | |
| 24.7013.0808 | - 8 | 1/2" | 1/2" | - 8 | 30,2 | 46 |
| 24.7013.0812 | - 8 | 1/2" | 3/4" | - 12 | 38,1 | 47 |
| 24.7013.1010 (a) | - 10 | 5/8" | 5/8" | - 10 | 34,0 | 50 |
| 24.7013.1012 | - 10 | 5/8" | 3/4" | - 12 | 38,1 | 50 |
| 24.7013.1212 | - 12 | 3/4" | 3/4" | - 12 | 38,1 | 48 |
| 24.7013.1216 | - 12 | 3/4" | 1" | - 16 | 44,5 | 51 |
| 24.7013.1616 | - 16 | 1" | 1" | - 16 | 44,5 | 52 |
| 24.7013.1620 | - 16 | 1" | 1.1/4" | - 20 | 50,8 | 57 |
| 23.7013.2020 * | - 20 | 1.1/4" | 1.1/4" | - 20 | 50,8 | 58 |
| 23.7013.2024 * | - 20 | 1.1/4" | 1.1/2" | - 24 | 60,3 | 68 |
| 23.7013.2424 * | - 24 | 1.1/2" | 1.1/2" | - 24 | 60,3 | 68 |
| 23.7013.2432 * | - 24 | 1.1/2" | 2" | - 32 | 71,4 | 71 |
| 23.7013.3232 * | - 32 | 2" | 2" | - 32 | 71,4 | 71 |

(a) Japanese flange, size according to **JIS** standards; not included in **SAE J518**

* On 1.1/4", 1.1/2" and 2" apply 23.7013

also available:

Balfit[®] Stainless Steel Spiral Straight SAE 3000 PSI (code 61) Flange

(add an 'S' at the end of the part number; ex: 24.7013.1212 S)

Construction characteristics and dimensions may be changed at anytime without prior notice

The data contained herein is for information purposes only and does not enlarge, amend or imply any warranty other than provided by the manufacturer with the product.

Any use of the product not in conformance with the manufacturer's instruction may be dangerous

Only items in this catalog are carried in stock. Some items are subject to minimum quantities or sold in multiples of standard quantities. Please refer to the price list or contact our commercial department. Prices subject to change without notice.

Balflex[®] - The European Technology

WWW.BALFLEXUSA.COM - (Ph) 713.928.6064 - (Fax) 713 928 6114 - (Email) sales@balflex.com