


Skive: 100R12, 4SH, 4SP

Balfit[®] Spiral Straight SAE 6000 PSI (code 62) Flange - 24.7016

solid-piece, carbon steel (code 62) flanged fitting for crimping on high pressure hydraulic hoses



According to ISO 6162 and ISO 12151-3 According to SAE J516 and SAE J518

Material: carbon steel, zinc plated

Ferrules : Balfit[®] ferrules series 20.400 and 20.403

Hoses: Balflex- Balmaster hoses SAE 100R9R / SAE 100R12 / DIN EN 856 4SP

may be also used on Balflex- Powerspir DIN EN 856 4SH hoses with Balfit ferrules series 20.403

part number	hose dash	hose Ø	Flange size	flange dash	D Ø Flange	C Cut Off
		inch	Inch		mm	mm
24.7016.0808	- 8	1/2"	1/2"	- 8	31,7	46
24.7016.0812	- 8	1/2"	3/4"	- 12	41,3	53
24.7016.1012	- 10	5/8"	3/4"	- 12	41,3	51
24.7016.1212	- 12	3/4"	3/4"	- 12	41,3	54
24.7016.1216	- 12	3/4"	1"	- 16	47,6	60
24.7016.1616	- 16	1"	1"	- 16	47,6	61
24.7016.1620	- 16	1"	1.1/4"	- 20	54,0	68
23.7016.2020 *	- 20	1.1/4"	1.1/4"	- 20	54,0	70
23.7016.2024 *	- 20	1.1/4"	1.1/2"	- 24	63,5	76
23.7016.2424 *	- 24	1.1/2"	1.1/2"	- 24	63,5	76
23.7016.2432 *	- 24	1.1/2"	2"	- 32	79,4	85
23.7016.3232 *	- 32	2"	2"	- 32	79,4	85

* On 1.1/4", 1.1/2" and 2" apply 23.7016

also available:

Balfit Stainless Steel Spiral Straight SAE 6000 PSI (code 62) Flange (add an 'S' at the end of the part number; ex: 24.7016.1212 S)

Construction characteristics and dimensions may be changed at anytime wthout prior notice

The data contained herin is for information purposes only and does not enlarge, amend or imply any warranty other than provided by the manufacturer with the product.

Any use of the product not in conformance with the manfacturer's instruction may be dangerous

Only items in this catalog are carried in stock. Some items are subject to minimum quantities or sold in multiples of standard quantities. Please refer to the price list or contact our commercial department. Prices subject to change without notice.

Balflex[®] - The European Technology